

EXPOSED FASTENER PANELS

GNMC 1/4" Corrugated

Panel Information:

Available Gauges:	28 GA, 26 GA, 24 GA
Substrate:	AZ 50 Galvalume on Painted material
Available Materials:	Painted, Galvalume, Galvanized, Bonderized, Cold Rolled
Paint Systems:	Multiple paint systems. Contact a GNMC representative for information.
Warranties:	Warranties are based on paint system. Contact a GNMC representative to discuss warranties.
Minimum Slope:	Not Recommended For Roofing
Panel Width/Coverage:	26"/24"
Panel Ribs:	1.25" On Center, 1/4" Tall

Panel Testing:

No panel testing at this time

Fastener Guide:

- #10 Woodfast screws are designed for use with dimensional lumber
- #14 Woodfast screws are designed for use with plywood sheathing, OSB and wafer wood (7/16" minimum thickness)
- #12 Tek screws are designed to be used with structural steel up to 3/16" thick

Roof Application:

We do not recommend this panel for roofing applications. Reach out to a GNMC representative to discuss options.


Wall Application:

Screws are to be installed no more than 2' up the panel. Predrilling is recommended to ensure water tightness. Must be installed over solid substrate.



24G AND 28G COLORS

Color chart options



**GREAT NORTHERN
METAL COMPANY**

(406) 624-0435
242 DURSTON ROAD SUITE B
BOZEMAN, MT 59718
gnmcusa.com