

EXPOSED FASTENER PANELS

GNMC PBR (Purlin Bearing Rib)

Panel Information:

Available Gauges:	26 GA, 24 GA
Substrate:	AZ 50 Galvalume on Painted material
Available Materials:	Painted, Galvalume
Paint Systems:	Silicon Modified Polyester
Warranties:	45 Year
Minimum Slope:	1/12
Panel Width/Coverage:	38"/36"
Panel Ribs:	12" On Center, 1.25" Tall

Panel Testing:

Hail Rating:	UL 2218 Class 4 Impact Resistance
Fire Rating:	UL 790 Class A
Uplift:	UL 580 Class 90

Fastener Guide:


- #10 Woodfast screws are designed for use with dimensional lumber
- #14 Woodfast screws are designed for use with plywood sheathing, OSB and wafer wood (7/16" minimum thickness)
- #12 Tek screws are designed to be used with structural steel up to 3/16" thick

Roof Application:

Screws are to be installed following the below details: installed following purlin spacing no more than 5'. Pre-drilling is recommended to ensure water tightness. It is recommended to use bead mastic between every panel at the side lap on roof slopes below a 4/12 with #12x3/4 Stitch screws installed every 2' up the panel.

Wall Application:

Screws are to be installed no more than 5' up the panel. Pre-drilling is recommended to ensure water tightness.





Light Gauge Panels

Color chart options



29G AND 26G COLORS



**GREAT NORTHERN
METAL COMPANY**

(406) 624-0435
242 DURSTON ROAD SUITE B
BOZEMAN, MT 59718
gnmcusa.com